

## PERFORMANCE SPECIFICATIONS

# **SUPRA 760**

**Supra 760** offers proven reliability, with millions of operating hours under the most demanding conditions.

**Supra 760** the finest truck refrigeration system on the market for delivering your product to market.

 The industry standard for reliability ensures lower overall cost of operation.

- Extended service intervals for maximum asset utilization.
- Exceptional capacity and air flow mean dependability and multi-application flexibility.
- The sleek, space-saving skin design is lightweight, low-noise, and damage-resistant.

### **Accessories and Options:**

Battery (dealer-supplied)
Battery box
30-gallon fuel tank
50-gallon fuel tank
Fuel heater
Top debris protection grille
High-voltage electric standby
460v-3ph-60Hz
Supply-air control
Stealth noise reduction kit
Host system door shutdown switch
Coolant heat system (diesel operation)
Electric heat system (standby operation)



#### **Condenser Dimensions**

71.7" x 33.7" x 24.7" (1,823 x 856 x 629 mm)

#### **Evaporator Dimensions**

48.2" x 24.9" x 11.1" (1,225 x 632 x 283 mm)

#### **Body Opening**

49.0" x 12.2" (1,245 x 310 mm)

#### **Approximate Weights:**

TDB-19: 933 lb (423 kg) without standby TDS-19: 978 lb (444 kg) with standby

Cooling/Temperature Capacity: Ambient at 100°F (38°C) Speed: 2,400 rpm diesel/60-hertz electric operation

Evaporator Return Air Temp.	Diesel Operation		Standby Operation	
	Btuh	Watts	Btuh	Watts
35°F ( 2°C) 0°F (-18°C) -20°F (-29°C)	20,000 12,000 7,500	5,860 3,520 2,200	18,000 11,000 7,000	5,275 3,225 2,055

#### **Standard Features Include:**

CT3-44 TriVortex diesel engine 05K12 2-cylinder compressor Long life spin-on lube oil filter Long life maintenance-free evaporator fan motors

Automatic hot-gas heating system Refrigerant R-404A

Three-way refrigeration valve system Standard with electric standby (model TDS)

Heavy-duty electric standby motor: 208v/230v-3ph-60Hz
Remote-mount power receptacle

Microprocessor control system
CAB COMMAND™ remote control center

Critical Cargo Monitor (in cab)
Audible temperature alarm (in cab)
Red light visual warning alarm (in cab)
Automatic pretrip system

Lighted CAB COMMAND keys Main on/off system power switch

Display indicators

Cool-Heat-Defrost Start/Stop-Out of Range Engine Operation-Electric Standby

Digital readout

CAB COMMAND (in cab)
Engine coolant temperature
Unit suction pressure
Battery voltage
Engine run hours
Electric standby hours

#### Standard Features (continued):

Maintenance interval hours Total on-time hours Setpoint temperature Box return-air temperature Automatic Start/Stop fuel saver City Speed control Automatic defrost control Extended-life antifreeze High coolant temperature protection High-power 70-amp alternator Heavy-duty dry air cleaner Low engine oil protection High refrigerant pressure protection Low refrigerant pressure protection Receiver tank pressure relief Bottom panel Installation package Electric fuel pump Fuel lines Battery cables Installation hardware

Fuel tank pickup tubes



Specifications are subject to change without notice.

Warranty: Product warranty and limitations are outlined in Form 62-10857. This warranty applicable only in North America. Consult your Carrier Transicold representative for warranty coverage elsewhere. Form 62-11661.







Carrier Transicold 700 Olympic Drive Athens, GA 30601 USA Tel: 706-357-7223 Fax: 706-355-5435

# Central America and Mexico

Ejercito Nacional 253-A Piso 5 Colonia Anahuac 11320 Mexico D.F. Ph: (5255) 5531-5010 Fax: (5255) 5531-5010 ext.1005

A member of the United Technologies Corporation family. Stock symbol UTX. ©2012 UTC Climate I Controls I Security. Printed in USA 0912.



Carrier Transicold Division Truck/Trailer Products Group P.O. Box 4805 Syracuse, NY 13221 USA